Irrigation Audit Checklist

A. Project & Auditor Information

Inspection Date	
Project Name	
Project Address	
Application Number	
Irrigation Auditor Name	
Irrigation Auditor Company	
Irrigation Auditor Address	
Irrigation Auditor Phone Number	
Irrigation Auditor Email	
Auditor Certified by:	
☐ Irrigation Association	
EPA WaterSense program	
Other:	

Note: For large projects or projects with multiple landscape installations (i.e. production home developments), an auditing rate of 1 in 7 lots or approximately 15% satisfies the audit requirement.

B. Audit Report

APPLICANT	Г		FOR AUDITOR	
			PASS	FAIL
	1.	Separate landscape customer service water meter or private submeter has been installed as applicable:		
		a. Non-residential projects: Greater than 1,000 sf landscape area		
		b. Residential projects: Greater than 5,000 sf landscape area		
	2.	The irrigation audit report includes:		
		a. System inspection		
		b. Inspect for leaks		
		c. System tune-up		
		d. Test the operating pressure of the irrigation system		
		e. Test to determine distribution uniformity		
		f. Test to determine precipitation rate of representative overhead irrigation valves		
		g. Confirm matched precipitation rates on valves with sprinkler heads, rotors and other emission devices		
		h. Report of any overspray or broken irrigation equipment		
		i. Report of overspray or run off that causes overland flow		
		j. Written recommendations to improve performance of the irrigation system		
		k. Preparation of an irrigation schedule, including configuring irrigation controllers with application rate, soil types, plant factors, slope, exposure and any other factors necessary for accurate programming		
		I. Other:		

C. Irrigation Equipment

APPLICANT	ITEN	ı	FOR A	UDITOR
			PASS	FAIL
	1.	Irrigation equipment is installed (location, type and size) as shown in the approved plans:		
		a. Automatic controller is ET-based or soil moisture-based and includes:		
		I. Irrigation scheduling parameters		
		II. Hydrozone map		
		b. Sensors installed include rain, frost (if necessary) and wind sensors (if necessary)		
		c. Point of connection includes:		
		I. Backflow prevention devices (if necessary)		
		II. Manual shut-off valve (gate, ball, butterfly valve)		
		III. Master shut-off valve		
		IV. Flow sensor for landscapes over 5,000 sf only		
		d. Valves (station)		
		I. Flow rate (gpm)		
		II. Application rates (in/hr)		
		III. Design operating pressure:		
		e. If static pressure is above or below required dynamic pressure of the system, pressure- regulating devices are installed		
	2.	Main and lateral lines		
	3.	Sprinkler heads		
		a. No spray heads within 24 inches of non-permeable surface		
		b. Sprinkler heads and other emission devices have matched precipitation rates		
		c. Swing joints or other riser protection provided in high traffic areas and areas near hardscape		
	4.	Low volume irrigation (drip, drip lines, and bubblers) is used in mulched planting areas (no spray irrigation) and in areas less than 10 feet wide		
	5.	Slopes greater than 25% are irrigated with an application rate not exceeding 0.75 inches per hour		
	6.	Runoff, low head drainage, overspray, or other similar conditions where irrigation water flows onto non-targeted areas are prevented		
	7.	Check valves or anti-drain valves are installed to prevent low head drainage		
	8.	Pressure regulating devices are used if the static water pressure at the connection of the public water system does not match the water pressure needs of the irrigation system		
	9.	Check irrigation legend and manufacturer's online data that sprinkler heads and other emission devices have matched precipitation rates		
	10.	Confirm that swing joints or other riser protection are provided in high traffic areas and areas near hardscape		

D. Hydrozones

APPLICANT	ITEM		FOR AUDITOR	
		PASS	FAIL	
	Match on the landscape plan and irrigation plan			
	2. Are irrigated by valves with similar site, slope, sun exposure, soil conditions, and plant materials with similar water use			
	3. Trees are on separate valves			
	4. Biotreatment areas are on separate valves			

E. Water Features

APPLICANT	ITEM	FOR A	UDITOR
		PASS	FAIL
	Use recirculating water systems		
	2. Use recycled water if available		

F. Irrigation Schedules

APPLICANT	ITEM	FOR A	UDITOR
		PASS	FAIL
	 Irrigation schedules have been developed, managed, and evaluated to utilize the minimum amount of water required to maintain plant health. Irrigation schedules shall meet the following criteria: 		
	a. Irrigation scheduling is regulated by automatic irrigation controllers		
	 Overhead irrigation is scheduled between 8:00 p.m. and 10:00 a.m. unless weather conditions prevent it 		
	 Irrigation schedules shall be regulated by automatic irrigation controllers using current reference evapotranspiration data (e.g., CIMIS) or soil moisture sensor data 		
	The irrigation schedules have been developed to include the parameters used to set the automatic controller and are submitted for each of the following:		
	a. Plant establishment period		
	b. Established landscape		
	c. Temporarily irrigated areas		
	3. Each irrigation schedule includes the following that apply for each station (valve):		
	a. Irrigation interval (days between irrigation)		
	b. Irrigation run times (hours or minutes per irrigation event to avoid runoff)		
	c. Number of cycle starts required for each irrigation event to avoid runoff		
	d. Amount of applied water scheduled to be applied on a monthly basis		
	e. Application rate setting		
	f. Root depth setting		
	g. Plant type setting		
	h. Soil type		
	i. Slope factor setting		
	j. Shade factor setting		
	k. Irrigation uniformity or efficiency setting		

6. Reviewer Comments		
	_	